


# DURACELL®

## TECHNICAL DATA SHEET

Type no.		DP 110L	
Article no.		010610480801	
EAN/GTIN no.		9005753088795	
Application		Starter battery	
Electrical data			
Rated voltage		12V	
Rated capacity		110 Ah (K20)	
Cold start current		800 A (EN)	
Dimensions and weights			
Box	COMPACT		
Length max.	344mm		
Width max.	172mm		
Box height max.	214mm		
Total height max.	230mm		
Battery weight	Ca. 29,0 kg (+/- 5 %)		
Electrolyte density		Approx. 1,28 kg/l	
Electrolyte		Diluted sulphuric acid	
Items/pallet		36	
Pallet ID		Euro pallet	
Items per layer		12	
Features			
Base hold-down		B00	
Layout		1	
Terminal		1	
Separator		PE bag separator	
Degassing		Battery with single degassing	
Flame arrester		Not integrated	
Performance identification		W3-C2-V2-E1	
Maintenance <sup>1)</sup>			
Water consumption		W3	
Refill water		Distilled or demineralised (DIN 43530)	
Self-discharge		Approx. 5 % per month	
Charging current		Approx. 1/10 of the rated capacity	
Charging voltage <sup>2)</sup>		max. 14,4 V	

<sup>1)</sup> All the listed values relate to room temperature +25° C

<sup>2)</sup> Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

Duracell Automotive c/o Banner GmbH

Banner Straße 1, A-4021 Linz, tel.: +43/(0)732/38 88-0, Fax DW-21599

e-mail: info@duracell-automotive.com, [www.duracell-automotive.com](http://www.duracell-automotive.com)



[duracell-automotive.com](http://duracell-automotive.com)