


DURACELL®

TECHNICAL DATA SHEET

| | | | |
|--------------------------------|--|--|--|
| Type no. | | DP145 SHD | |
| Article no. | | 018645030801 | |
| EAN/GTIN no. | | 9005753086296 | |
| Application | | Starter battery | |
| Electrical data | | | |
| Rated voltage | | 12V | |
| Rated capacity | | 145 Ah (K20) | |
| Cold start current | | 800 A (EN) | |
| Dimensions and weights | | | |
| Box | | A | |
| Length max. | | 513mm | |
| Width max. | | 189mm | |
| Box height max. | | 195mm | |
| Total height max. | | 220mm | |
| Battery weight | | Ca. 37,0 kg (+/- 5 %) | |
| Electrolyte density | | Approx. 1,28 kg/l | |
| Electrolyte | | Diluted sulphuric acid | |
| Items/pallet | | 24 | |
| Pallet ID | | Euro pallet | |
| Items per layer | | 8 | |
| Features | | | |
| Base hold-down | | B00 | |
| Layout | | 3 | |
| Terminal | | 1 | |
| Separator | | PE bag separator with glass nonwoven | |
| Degassing | | Battery with central degassing | |
| Flame arrester | | Integrated | |
| Performance identification | | W4 - C2 - V3 - E3 | |
| Maintenance ¹⁾ | | | |
| Water consumption | | W4 | |
| Refill water | | Distilled or demineralised (DIN 43530) | |
| Self-discharge | | Approx. 3 % per month | |
| Charging current | | Approx. 1/10 of the rated capacity | |
| Charging voltage ²⁾ | | max. 14,8 V | |



¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

Duracell Automotive c/o Banner GmbH

Banner Straße 1, A-4021 Linz, tel.: +43/(0)732/38 88-0, Fax DW-21599

e-mail: info@duracell-automotive.com, www.duracell-automotive.com



duracell-automotive.com